

3991 Green Park Road St. Louis, Missouri 63125 Phone: 314.631.1416 www.ductformer.com

Not just another knock-off or copy, but a totally new design with the Quality, Reliability & Fair Price you expect.

The **Model CR8** is the work horse of the Ductformer Line. It can accommodate up to four (4) sets of tooling. Ductformer's CR8 Rollformers are designed with versatility and flexibility in mind. Multiple roll tool configurations are available on the CR8 including Slip and Drive Cleats, Male and Female Snap-Lock, Pittsburgh, Acme Seams, Tri-Plex and Standing Seam.

Sealed Roller Bearings

- Keep Metal Particles Out of Bearings
- Eliminates External Thrust Bearings

All New Computer-Aided Design

- All Hardened Roll Tooling
- Eliminates Pittsburgh Opening Rolls



Quality Made In U.S.A.

- All Gear Drive
- Full Hardened Tool Steel
 Infeed Guides
- 16-28 gauge capacity
- Speed 85 Feet Per Minute
- 5 H.P. 240/480 V, 60 Cycle, 3-Ph
- Fully Enclosed Machine Base
 69" Long x 24" Wide x 40" Tall
 34" Pass Line
- Shipping Weight: 900 Pounds
- Many Roll Tooling Options





3991 Green Park Road St. Louis, MO 63125 Phone: 314.894.3903 www.Ductformer.com

======================================				
MAT. USED	SIZE	SHAPE	TYPE & CAPACITY	
3-13/16"	1-1/16" Pocket	1-1/16"	Flat 'S' 22-28 Gauge	
2-1/8"	1-1/8" Wide	1-1/8"	Drive Cleat 22-28 Gauge	
OPTIONAL OUTBOARD ROLLS				
MAT. USED	SIZE	SHAPE	TYPE & CAPACITY	
1"	5/16" Pocket _	5/16"	Pittsburgh Lock 20-26 Gauge	
1-5/16"	3/8" Pocket	3/8"	Pittsburgh Lock 18-24 Gauge	
1-13/16"	1/2" Pocket _	1/2"	Pittsburgh Lock 16-20 Gauge	
1-1/8"	3/8" Seam	3/8"	Double Seam Lock 20-28 Gauge	
1-1/2"	7/16" Pocket	1/2"	Female Button Snap Lock 22-28 Gauge - \$1,775	
1-3/4"	9/16" Pocket	5/8"	Female Button Snap Lock 20-26 Gauge - \$1,815	Combination Male/Female
7/16"	7/16" High		Male Button Snap Lock 20-28 Gauge - \$1,450	
1/4" to 9/16"	1/4" High to 9/16" High	9/16"	Right Angle Flange 20-28 Gauge	
1-1/8"	5/8" High	5/8"	1 _{16"} Standing Seam 22-28 Gauge	l Triplex Rolls Three-In-One
1-3/4"	5/8" High	5/8"	Tap-In Lock 22-28 Gauge	